

ZZ® 880 Fire Protection Module

Technical data sheet

Trade name:	ZZ® 880 Fire Protection Module
Material:	ZZ® 18-A Fire Protection Foam ZZ-Fire protection foam BDS-N, variant A
Description:	Soft-elastic intumescent polyurethane foam with halogen-free flame retardants; does not exhibit any appreciable expansion pressure.
Implementation areas:	As a moulded component (3D moulded component, toroidal sealing ring, panel, blank) for use as a sealing system for cable and pipe penetrations, joint seals, small surface insulation.
Product group:	IN16 – Interior seals EX12 – Exterior seals
Certificates:	<ul style="list-style-type: none">• Classification report no. 19/0434, Currenta• Test report no. 17/0798• Test report no. 17/0910
Requirement set:	R22, R23 according to EN 45545-2
Hazard level:	HL1, HL2, HL3
Colour:	Red-brown
Transport / storage:	Dry and only in the original packaging
Storage temperature:	5 °C to 30 °C
Bulk density:	$\rho \geq 180 \text{ kg/m}^3$ to 750 kg/m^3
Safety notices:	Contains melamine (SVHC; CAS 108-78-1, EC no. 203-615-4) > 0.1% (Please note the safety data sheet).

ZZ® 880 Fire Protection Module**Behaviour in the event of fire****Classification of the
fire behaviour according to
DIN EN 13501-1:**

Class E

Expansion pressure:

No expansion pressure measurable

Foaming factor:

1.6x to 4.5x

Tested on samples at 450 °C for more than 25 minutes with superimposed load. The foaming factor is a laboratory characteristic value. The foaming behaviour in installed status depends on the existing boundary conditions.

**Smoke generation
according to EN ISO 5659-
2:** $D_s \text{ max } (-) = 57$ **Burning behaviour
(Oxygen index)
according to ISO 4589-2:** $OI = 69.9 \%$ **Conventional index of
toxicity according to
NF X 70-100-1 /-2:** $CIT_{NLP} = 0,30$ **Surface flammability
according to ASTM E 162:**Flame spread index $I_s = 14.2$ **Specific optical density of
smoke according to
ASTM E 662:**Non-flaming mode $D_s (1.5) (-) = 34$ $D_s (4.0) (-) = 80$ Flaming mode $D_s (1.5) (-) = 36$ $D_s (4.0) (-) = 84$ **Physical construction material / product characteristics**

The following specifications do not represent guaranteed product characteristics. They must, therefore, be regarded exclusively as information intended to serve as guideline values.

Thermal conductivity: $\lambda = 0.103 \text{ W/(m}^{\circ}\text{K)}$

Test standard: DIN EN 12667

Surface resistance: $R_0 = 2.39 \times 10^9 \Omega$

Test standards: DIN EN 60079-0 (VDE 0170-1):2013-04 Section 7.4 including application of note 2 of Section 7.4.2, IEC 60079-0:2011 and modified + Cor.:2012, EN 60079-0:2012, EN 80079-36 and TRGS 727:2016-07-29

ZZ® 880 Fire Protection Module**Hygiene, health and environmental protection****Indoor air hygiene**

Requirements of AgBB Scheme 2015 are fulfilled
Test standards: prEN 16516, ISO 16000-3, ISO 16000-6,
ISO 16000-9

Test lab: eco-INSTITUT Germany GmbH, Cologne
Date: 25/08/2017

	Result	Requirement	Requirements fulfilled
Emission rating			
Measurement after 3 days			
TVOC (C6 – C16)	0.008 mg/m ³	≤ 10 mg/m ³	✓
Carcinogens (EU Cat. 1A and 1B)	< 0.001 mg/m ³	≤ 0.01 mg/m ³	✓
Measurement after 28 days			
TVOC (C6 – C16)	0.014 mg/m ³	≤ 1 mg/m ³	✓
Σ SVOC (C16-C22)	< 0.005 mg/m ³	≤ 0.1 mg/m ³	✓
R (dimensionless)	0.02	≤ 1	✓
VOC without NIK	< 0.005 mg/m ³	≤ 0.1 mg/m ³	✓
Carcinogens	< 0.001 mg/m ³	≤ 0.001 mg/m ³	✓

VOC emission class

A+ in accordance with French decree no. 2011-321
Test standards: ISO 16000-3, ISO 16000-6,
ISO 16000-9, ISO 16000-11, ISO 16017-1

**Microbial
metabolisation:**

Inert / fungistatic / bacteriostatic
Test standard: DIN EN ISO 846

ZZ® 880 Fire Protection Module

Other product characteristics

Influence of coating materials and chemicals

The following paints and occasional, brief influence of chemicals do not cause any change in the technical fire protection properties:

Coating materials: Dispersion paint, alkyd resin paint, polyurethane acrylic lacquer, epoxy resin lacquer

Solvent/oil: Trichloroethylene, xylene, acetone, white spirit, butyl acetate, butanol, domestic fuel oil

Gaseous chemicals: Brief storage over concentrated ammonia solution

Comment: Environmental conditions with high humidity levels and/or some coating materials and chemicals can cause minor lightening of the colour.

Contact with metals and plastics

The surface consistency of aluminium, stainless steel, galvanised steel and plastics made of polyethylene and polyvinyl chloride is not negatively affected upon contact with "Fire Protection Foam ZZ 18-A".

All the information in this leaflet is based on current technical knowledge and experience. Details on processing and application must be checked on a project-by-project basis due to the variety of possible influences.

If the application for which our products are used is subject to a government agency approval obligation, then the user is responsible for obtaining this approval. We would be pleased to respond to any enquires you might have.

The information in this document and declarations of Karl Zimmermann GmbH in conjunction with this document do not constitute any assumption of a guarantee. Guarantee declarations require the separate, express written declaration of Karl Zimmermann GmbH.

The conditions specified in this data sheet represent the characteristics of the delivery object, they do not represent any specific values. Specific values must be separately determined on a case-by-case basis.

We reserve the right to adapt the product to technical progress and to new developments.

In all other aspects we refer to our general terms and conditions.